

FM/IIP Conference Discussion System

FM/CTL120L Control Console



Technical Data

- Power supply AC110/220V 50/60Hz
- Maximum output 100W
- Maximum capacity Microphone units x 60
- Dimension (LxWxH) 435x269x74mm(2U)
- Net weight Approx. 4kg
- Color & case material Silver white painted iron housing
- Working temperature 0°C- 40°C

Configuration

- AC power fuse 1.0amp,220V x 1
1.0amp,110V x 1
- DC power fuse 10 amps x 1
- Status indicator Audio signal overload LED x 3
Audio signal output LED x 3
- Monitor 50mm loudspeaker
- Input AUX IN x 1.0dBV, unbalance
MIC IN x 1600Ω, -69dB, unbalance
- Output PA OUT x 1.0dBV, unbalance
AUX OUT x 1.0dBV, unbalance
REC OUT x 1., 10kΩ, -20dBV, unbalance
Monitor headphone output x 1
- Operation mode Microphone limiter : 1,2,4,6
Free mode(no limitation)
- Control AUX IN volume x 1
MIC IN volume x 1
PA OUT volume x 1
AUX OUT volume x 1
Mic built-in loudspeaker volume x 1
Monitor loudspeaker volume x 1
Treble volume x 1
Bass volume x 1
- Microphone port 4 terminals for 4 groups each 30 max.

