

FM/ISO Two Channel Console



Technical Data

- Power supply AC110/220V 50/60Hz
- Maximum output 100W
- Maximum capacity Microphone units x 80
- Channel frequencies CH1 95KHz
CH2 135KHz
- Modulation FM
- Distortion factor < 1.5%
- Signal-to-noise ratio > 50dB
- Cross-talk attenuation > 50dB
- Power Supply AC110/220V
- Maximum consumption 110W
- Dimension (LxWxH) Approx. 435x269x74mm(2U)
- Weight Approx. 4kg
- Color & Case material Silver white painted iron housing

Configuration

- AC power fuse 1amp. 220V x 1
2amp. 220V x 1
- DC power fuse 10 amps x 1
- Status indicator Audio signal overload LED x 3
Audio signal output LED x 3
- Monitor 50mm loudspeaker
- Input AUX IN x 1.0dBV, unbalance
MIC IN x 1600 Ω , -69dB, unbalance
- Output PA OUT x 1.0dBV, unbalance
AUX OUT x 1.0dBV, unbalance
REC OUT x 1., 10k Ω , -20dBV unbalance
Monitor headphone output x 1
- Operation mode Microphone limiter: 1,2,4,6
Free mode (no limitation)
- Control AUX IN volume x 1
AUX OUT x 1.0dBV, unbalance
REC OUT x 1., 10k Ω , -20dBV unbalance
Monitor headphone output x 1
Mic built-in loudspeaker volume x 1
Monitor loudspeaker volume x 1
Treble volume x 1
Bass volume x 1
- Radiator connection BNC female socket x 2
- Link socket for interpreter microphone x 1
- Recording Output Recording output socket for Ch#1 and Ch#2