

ISO6001 Infrared Console



Technical Data

- Number of channels 6
- Channel frequencies
CH1 95KHz
CH2 135KHz
CH3 175KHz
CH4 215KHz
CH5 255KHz
CH6 295KHz
- Modulation FM
- Distortion factor < 1.5%
- Signal-to-noise ratio > 50dB
- Cross-talk attenuation > 50dB
- Power Supply AC110/220V
- Maximum consumption 110W
- Dimension (LxWxH) 435x294x112mm(2U)
- Weight Approx. 6kg
- Color & Case material Silver painted panel

Configuration

- Mains power switch x 1
- AC power fuse 1amp. 220V x 1
2amp. 220V x 1
- DC power fuse 4amps x 1
- Status indicator Input status overload LED
- Connector Original signal input LED x 1
Radiator operation LED x 1
Mains power LED x 1
Infrared signal output LED x 1
15V Power LED x 1
24V Power LED x 1
IR Testing LED x 1
- Control Input signal volume x 1
Radiator operation LED x 1
- Channel status Interpretation status LED x 1
- indicator Voice signal peak LED x 6
Audio signal output LED x 6
Channel ON/OFF LED x 6
- Interpreter A36K-SP female socket x 2
- Console connector
- Radiator connector BNC socket x 2
- Original signal input 1/4" jack socket x 1
- Recording output RCA female socket x 6
- Playback output RCA female socket x 6